

**GUEST Cruising Chargers**

Guest Cruising Chargers are made specifically for a coastal, blue water environment where top quality, rugged equipment is required. They feature individual circuit boards, which provide each battery its own specific charging circuit. The benefit is a well designed charging system that protects your battery investment. Guest Cruising Chargers also function as a continuous 12 Volt power supply to run your DC accessories while at the dock.



ORDER NO.	BANKS	TOTAL AMPS	DIMENSIONS	PRICE
GST 2614A	Dual 10/5	15	9.84" x 9.60" x 2.92"	\$375.40
GST 2622A	Dual 10/10	20	9.84" x 9.60" x 2.92"	\$456.24
GST 2633A	Dual 20/10	30	12.96" x 9.84" x 2.92"	\$685.06
GST 2621A	Triple 10/5/5	20	9.84" x 9.60" x 2.92"	\$488.45
GST 2632A	Triple 20/5/5	30	12.96" x 9.84" x 2.92"	\$542.77

**ProMariner**

**ProMariner Pro Tech I-Series Automatic Marine Battery Charger**

The ProTech i-Series is designed to deliver performance and value by employing proven advanced electronic technology with added innovative styling and features like: wide range global AC input, user programmable battery type selector and active battery balance control on select models.

- 4 complete stages, for fast charge times, conditioning, maintenance of each battery & dockside power supply mode
- User Programmable Battery Type Selector for use with Lead Acid, AGM and GEL Batteries
- User Programmable Conditioning Mode 1 to 4 Hours
- Fully Automatic Wide Range Global AC Input, select 95VAC — 250VAC 50/60Hz
- Ignition protection, over temperature, over voltage and reverse polarity protection



ORDER NO.	VOLTS	AMPS	HEIGHT	WIDTH	LENGTH	BANKS	PRICE
PRO 63310	12	10 Amp	2.9"	6.4"	10.5"	2 Bank	\$218.75
PRO 63315	12	15 Amp	2.9"	6.4"	10.5"	3 Bank	\$306.20
PRO 63320	12	20 Amp	2.9"	6.4"	10.5"	3 Bank	\$382.79
PRO 63331	12	30 Amp	2.9"	6.4"	10.5"	3 Bank	\$507.98
PRO 63341	12	40 Amp	2.9"	6.4"	15.5"	3 Bank	\$546.85

**ProMariner Battery Bank Cable Extender**

Use with all On-Board Marine Battery chargers when standard battery charger cables do not reach you bow, center mount or stern battery compartment locations.

- No cutting, stripping or butt splicing of wire required
- Marine U.L. grade cable rated up to 30 amps
- Fully tinned wiring and gold plated hardware for anti-corrosion
- Dual integrated in-line fuses for maximum cable protection
- Color coded for easy installation

ORDER NO.	LENGTH	PRICE
PRO 51071	5'	\$19.87
PRO 51070	15'	\$28.65



**Charles HQ Battery Chargers**

Meet ABS and USCG requirements for megayacht and workboat fleets around the world.

**FEATURES**

- Agency approvals: Meets ABS (38G), Marine UL (1236), US Coast Guard (10B) and ABYC (A-31) requirements
- LED indicator pilot lamp
- Quick disconnect on/off switch on front cover
- Separate voltmeter and ammeter
- Internal failure alarm (ready), customer to provide indicator
- Multi-bank (3), multi-stage (bulk, absorption and float) battery charger
- Ability to work as power supply
- Voltage and current limiting ability
- Thermal, over-current, ignition and reverse-polarity protected
- Input and output fusing
- Constructed with heavy-duty, corrosion resistant, UL recognized materials
- Designed to run cool, quiet and EMI/RFI interference free
- Temperature compensation - built for optimal performance in a variety of ambient temperatures
- 50/60Hz for international and U.S.A. applications
- Drip shield (necessary) included
- 5-year manufacturers limited warranty
- Made in the U.S.A.



ORDER NO.	DESCRIPTION	PRICE
CMP 9Q12455HQA	45 AMP 12V ABS	\$815.14

**ProMariner**

**ProNautic Series**

ProNautic employs ProMariner's progressive C3 all digital technology, bolstering intuitive software-based multi-stage charging, communication and control. C3 yields precision charging performance, programmable charge profiles and real time status. Optional helm remote available.

- Intelligent C3 Software Controlled Multi Stage Charging  
Optimal fast charge, conditioning, maintenance & dockside power supply mode
- Active Battery Balance Control (BBC)  
C3 Software actively monitors the condition of each battery or bank while charging, to ensure no battery is ever overcharged
- C3 Intelligent Self Calculating Absorption / Conditioning Mode  
ProNautic automatically programs charge/conditioning time based on discharge state of batteries, resulting in a 100% charge while desulfating batteries and extending battery life
- C3 Automatic 10 Day Re-Condition Mode  
Added conditioning to maximize battery life
- Fully Automatic Wide Range Global AC Input 95VAC to 250VAC 50/60hz
- True Temperature Compensation with Remote Probe
- Built In Safety  
Ignition protection, over temperature, over voltage and polarity protection
- 40 & 50 AMP: 17"L x 8.25"W x 3.75"H
- 60 AMP: 18.75"L x 8.25"W x 3.75"H



ORDER NO.	VOLTS	AMPS	BANKS	PRICE
PRO 63540	12	40	3	\$699.89
PRO 63550	12	50	3	\$818.99
PRO 63560	12	60	3	\$956.55