



Electro Scan

Electro scan consistently controls the electrodes to reduce power consumption by up to 36%. New LCD Display provides detailed information on system.

- Can be used with both manual and electric toilets.
- Generates its own natural disinfectant from salt water.
- Treats each flush as waste is generated.
- Discharges with treatment levels that are safe for environmentally sensitive areas.
- Easy to install.

Options:

- 12V DC
- Optional salt feed systems available when using fresh or brackish water



ORDER NO.	PRICE
RAR EST12	\$1560.52

GROCO® WASTE MACERATOR PUMP

THE CONCEPT

155 Series waste macerator pumps makes fast work (17 GPM) of holding tank pump-out. Since waste is macerated BEFORE it leaves the tank, smaller hose and overboard seacock (3/4") may be used in the discharge line.

Tank Depth 10 inches
12 volt

Note: New pump installations require GROCO #MP Hardware (tank hardware kit), ordered separately.

Service Note: 155 Series will fit the same mounting used for discontinued MPT or MPS series macerator pumps.



ORDER NO.	PRICE
GRC 155611012	\$598.00



Salt Feed Tank For Electro Scan

The Electro Scan MC System requires ocean grade salt water in order to process properly. If the vessel is operated in brackish, fresh water, cold water or the toilet system utilizes on board fresh water to operate, there is a need to increase the amount of salt in the flushing water to operable levels that will allow the treatment units process to occur. The Electro Scan will not function if the amount of salt in the treatment unit is lower than its tolerable operating range. This is where the salt feed system becomes a necessary addition to the installation. 12 volt.



ORDER NO.	DESCRIPTION	PRICE
RAR 323003	4 gallon w/ pump	\$570.08



Sea Era Conversion Kit

An inexpensive way to replace your electric or manual toilet. Save the toilet bowl and seat and replace the lower base.

- Benefits:**
- Economical electric macerating marine toilet.
 - Sea Water models can be run dry without damaging the pump.
 - Low power consumption and quieter operation for on-board pressurized freshwater models.
 - Heavy-duty marine push button switch is included.

ORDER NO.	DESCRIPTION	PRICE
RAR 160LF012	Freshwater Version	\$560.47
RAR 160LI012	Raw water version	\$538.87

Options:

- Available in raw water with integral intake pump or on-board pressurized freshwater lower base models.



NEW



Electric Toilet Conversion Kit

Converting a manual marine toilet to simple pushbutton electric operation is easy with the toilet conversion kit. It can be fitted with the Raritan P.H. or Compact, Wilcox Crittenden "Head Mate", Groco HC, PAR or Brydon 59128-Series, and virtually any other marine toilet using 3-3/4" diameter bolt circle with a 4-hole pattern base.

The self-priming flexible impeller flush pump rinses the bowl while the powerful macerator scavenger pump grinds up and pumps out waste. A built in backflow preventer is included in discharge. A heavy duty push-button switch and 1" to 1-1/2" hose adapter for the discharge port and all clamps and fasteners to complete the conversion are included.

Inlet 3/4", discharge 1".




ORDER NO.	VOLT DC	AMPS/FUSE SIZE	PRICE
ITT 370100092	12	18/25	\$737.51

ORDER NO.	DESCRIPTION	PRICE
ITT 370400000	Seal and Gasket Service Kit	\$54.70
ITT 370410010	Replacement Pump	\$248.71

Macerator Pump

Grinds waste into small particles for easy discharge.

Fully enclosed with stainless steel shaft. Includes Run Dry Protection with self-priming Flexible Impeller and Stainless wearplate making this pump the ideal solution for emptying marine holding tanks. The unit is self-priming to a 5' lift when wet. The macerator section grinds waste to 1/8" or smaller. Flow rate is 12 GPM.



ORDER NO.	VOLT	AMPS	INLET	PRICE
ITT 185902092	12	15/20	1-1/2" NPT	\$282.83
ITT 185981000			Service Kit	\$58.51
ITT 63030003			Impeller	\$20.64

Electric Flush Pump -

CONVERTS JABSCO MANUAL TOILETS TO ELECTRIC CONVENIENCE...

The Electric Flush Pump converts all Jabco manually operated toilets to convenient electric operation. With the optional adapters it can be installed on almost any manual toilet. Once converted, the toilet is flushed by simply turning the large control knob on the top of the pump assembly. The self-priming flushing pump rinses the toilet bowl while the waste pump macerates and evacuates the waste. The operator selects from two operating modes to either flush the toilet bowl or drain it. The spring-loaded control knob always returns to the off position. Inlet port fits 3/4" hose. Height 10-1/2", width 4", depth 7-3/4".



ORDER NO.	VOLT	AMP	FUSE	PRICE
ITT 292000120	12	24	25	\$550.00

ORDER NO.	DESCRIPTION	PRICE
ITT 291010000	Impeller Kit	\$72.15